

Serial No.: 09/901,577
Docket No.: KOKUSAI069
ORI.038

AMENDMENTS TO THE CLAIMS:

1. (Currently Amended) A remote control system for one or more semiconductor manufacturing apparatuses ~~capable of accessing~~ comprising:

a supervisory device ~~[[of]]~~ which controls said one or more semiconductor manufacturing ~~apparatuses from~~ apparatuses; and

a remote operation device that accesses said supervisory device through a communication line,

wherein upon accessing said supervisory device, said remote operation device simultaneously displays the same screen as that displayed ~~[[in the]]~~ by said supervisory device, and enables said remote operation device to perform the same operations as those carried out by said supervisory device ~~to be performed~~ on said one or more semiconductor manufacturing apparatuses.

2. (Currently Amended) The remote control system for one or more semiconductor manufacturing apparatuses according to claim 1, wherein said supervisory device performs user authentication when said remote operation device ~~is connected~~ connects to said supervisory device.

3. (Currently Amended) ~~A semiconductor manufacturing apparatus connected to said supervisory device accessible to said remote operation device~~ The remote control system for one or more semiconductor manufacturing apparatuses according to claim [[1]] 1, wherein

Serial No.: 09/901,577
Docket No.: KOKUSAI069
ORI.038

upon accessing said supervisory device, said remote operation device simultaneously displays the same screen as that displayed in the said supervisory device.

4. (Currently Amended) ~~A remote operation device for use with said~~ The remote control system for one or more semiconductor manufacturing apparatuses according to claim [[1]] 1, wherein said supervisory device includes an IP routing function for achieving remote control operation from said remote operation device.

5. (Currently Amended) A remote control system for one or more semiconductor manufacturing apparatuses comprising:

~~a local area network system including~~ a host device operably connected to said [[and]] one or more semiconductor manufacturing apparatuses; and

a remote operation device [[with]] including a communication element ~~accessible to~~ that accesses said host device ~~on the semiconductor manufacturing side~~ by way of a communication line;

wherein said host device is provided with an IP routing function ~~and protocols necessary~~ for achieving remote control operation from said remote operation device, and a communication element having a call incoming function [[of]] for receiving a call incoming from said communication line, and

said host device ~~serves to perform~~ performs user authentication when said remote operation device ~~tries to connect~~ connects to said host device, ~~so that~~ wherein upon authentication said remote operation device ~~thus authenticated can display~~ simultaneously

Serial No.: 09/901,577
Docket No.: KOKUSAI069
ORI.038

displays the same screen as that displayed on said host device, permitting said remote operation device to remotely control and operate said host device.

6. (Currently Amended) The remote control system for one or more semiconductor manufacturing apparatuses according to claim 5, wherein said host device and said remote operation device each have a modem as said communication element for enabling connection between said host device and said remote operation device through one of an analog line ~~[[or]]~~ and an analog network.

7. (Currently Amended) The remote control system for one or more semiconductor manufacturing apparatuses according to claim 5, wherein said host device and said remote operation device each have a terminal adapter as said communication element for enabling connection between said host device and said remote operation device through one of an ISDN line ~~[[or]]~~ and a network.

8. (Currently Amended) A remote control system for one or more semiconductor manufacturing apparatuses comprising:

a local area network system ~~including~~ comprising a plurality of host devices each connected with one or more semiconductor manufacturing apparatuses, and a router ~~as its communication element~~ connected with said host devices; and

a remote operation device ~~[[with]]~~ including a router ~~as its communication element~~ ~~accessible to~~ that accesses said host devices ~~on the semiconductor manufacturing apparatus~~

Serial No.: 09/901,577
Docket No.: KOKUSAI069
ORI.038

side by way of a communication line;

wherein said host devices are each provided with an IP routing function ~~and protocols necessary~~ for achieving remote control operation from said remote operation device, and a communication element having a call incoming function ~~[[of]]~~ for receiving a call incoming from said communication line, and

said host devices each ~~serve to~~ perform user authentication when said remote operation device ~~tries to connect~~ connects to said host devices, so that said remote operation device thus authenticated can individually simultaneously display the same screen as that displayed on each of said host devices, permitting said remote operation device to remotely control and operate said host devices.

9. (Original) The remote control system for one or more semiconductor manufacturing apparatuses according to claim 8, wherein said communication line connecting between said host devices and said remote operation device comprises the Internet.

10. (Currently Amended) The remote control system for one or more semiconductor manufacturing apparatuses according to claim 8, wherein said communication line connecting between said host devices and said remote operation device comprises one of a local area network ~~[[or]]~~ and a wide area network.

11. (Currently Amended) A remote control system for one or more semiconductor manufacturing apparatuses comprising:

Serial No.: U
Docket No.: KOKUSAI069
ORI.038

a local area network system ~~including~~ comprising a plurality of host devices each connected with ~~one or more~~ at least one semiconductor manufacturing ~~apparatuses~~ apparatus, and an access server ~~as its communication element~~ connected with said host devices; and

a plurality of remote operation devices ~~with a plurality of~~ each having a communication ~~elements, respectively,~~ element accessible to said host devices ~~on the semiconductor manufacturing apparatus side~~ by way of a ~~plurality of~~ communication ~~networks~~ network;

wherein said host devices are each provided with an IP routing function ~~and protocols~~ necessary for achieving remote control operation from each of said remote operation devices, and

said host devices each ~~serve to~~ perform user authentication when each of said remote operation devices ~~tries to connect~~ connects to said host devices, ~~so that~~ wherein each of said remote operation devices thus authenticated can individually simultaneously display the same screen as that displayed on each of said host devices, permitting said remote operation devices to remotely control and operate said host device devices.

12. (Currently Amended) The remote control system for one or more semiconductor manufacturing apparatuses according to claim 11, wherein said ~~plurality of~~ communication ~~networks~~ network connecting between said host devices and said remote operation devices ~~include~~ comprises at least one of a public telephone network, an ISDN network, the Internet, a local area network and a wide area network.

Serial No.: 09/901,577
Docket No.: KOKUSAI069
ORI.038

13. (New) The remote control system for one or more semiconductor manufacturing apparatuses according to claim 5, wherein said remote operation device enables same operations as those carried out by said host device.

14. (New) The remote control system for one or more semiconductor manufacturing apparatuses according to claim 8, wherein said remote operation device enables same operations as those carried out by said host devices.

15. (New) The remote control system for one or more semiconductor manufacturing apparatuses according to claim 11, wherein each of said remote operation devices enables same operations as those carried out by said host devices.